

# Demolition Kit

Art.Nr. 0202100



## Technical features

Blasting Machines	KSP 400	KSP 700
Ignition voltage	DC 380V	DC 700V
Filling time of capacitor		up to 6 s.
Capacitor capacity	200mF	50mF
max. no. of activations		120
Battery voltage		DC 10V
Type of battery		MOTOROLA NTN 5521
min. voltage of battery		DC 9,2V
Battery capacity		1,1Ah
Temperature range from		-20oC to +70oC
Case		ABS plastic
max. net resist. for min. ignition power 1A	300W	600W
max. No EDK for serial net		180 pieces
max. No EDK for parallel net		3 pieces
Connectors are short-circuited until the moment of activating		
Controlled activating of EDK		



### Battery Charger for Blasting Machines

Charging time	60Min
AC input	220V
Dimension	60 x 200 x 85 mm
Weight	1200g



### VICTORINOX Swiss Tool

Weight	314g
--------	------

A Multifunction Pocket Toolkit is made of first class stainless steel. It consists of: pliers / screwdriver 2, 3, 5 & 7,5mm, / wire cutter for wire up to a hardness of 40 HRC / cap lifter / normal blade / serrated blade / metal file / metal saw / wood saw / reamer and punch / Philips screwdriver 1+2 / chisel/scrapper / strong crate opener / wire bender / wire stripper / wire scraper / can opener / 230mm ruller / 9 inches ruller / electrical crimper and lanyard hole



### Box for Electric Cap

Schachtel aus schwarzem Cordura mit Plastikeinlage für 15 Zündkapseln	
Dimension	40 x 180 x 90 mm
Weight	125 g



### Cap Box

Plastic box for 12 cap's	
Dimension	20 x 80x 60 mm
Weight	80 g



### Digital Galvanometer

Black kordura box	
Weight	285g
Dimension	70x130x35
Resistance	200Ohm - 20MOhm
VDC	200mV - 600V
VAC	200V - 600V
ADC	200mA - 10A

## Double Firung Wire

Length	500 m
Resistance	30Ohm + 30Ohm

## Cap Crimper



Aluminium/Steel	
Protection tube in case unwanted detonating of crimping cap	
Six-edged shape	5 mm
Weight	510 g
Length	220 mm

## Carrying Bag



black Cordura	
Dimension	390 x 250 x 170 mm
Weight	1500 g