

RF Series

Art.No. 0300500



EODPartner has recognized the need of many government and law enforcement agencies requiring a communications “dead zone”. As such, we are pleased to provide the following standard models for your review. Feel free to contact us with your specific requirements.

Features

- One Switch Operation with Trigger Guard
- Continuous Power Monitoring
- Removable Filters (Intake & Exhaust)
- Convenient Carrying Handles
- Front Panel Operation Indicators
- Instant On – Solid State Design
- TTL Inhibit (so that you can use your own communications)
- Quick disconnect Power Source
- Tread Plate Top for Personnel safety

Specifications

Model	TX Frequency	Noise Type	Power
RFJ7	134 – 174 MHz 400 – 512 MHz	Broadband Noise	50 watts **
RFJ8	20 MHz – 512 MHz	Broadband Noise	50 watts **
RFJ9	20 MHz – 1 GHz	Broadband Noise	25 watts **
RFJ10	20 MHz – 3 GHz	Broadband Noise	25 watts **
RFJ11	20 MHz – 4.2 GHz	Broadband Noise	25 watts **
RFJ12	20 MHz – 12 GHz	Broadband Noise	per request
RFJ13	4.2 GHz – 18 GHz	Broadband Noise	20 watts **
RFJ14	18 GHz – 26.5 GHz	Broadband Noise	40 watts **

Dimensions	10.5“(H) x 19“(W) x 28“(L)
Weight	110 pounds
Temperature Range	-30° - +130°
Humidity: Tripods	95%
Power Requirements	12VDC 24VDC 110VAC 220VAC
Options	Bullet Proof Case (30.06) Discone Antennas Directional Antennas Pressurized cases Electronic Cooling Tripods Vehicle Mounts Shock Mounting